




ATPV 19 & 24 CAL Arc H2O FR Hi-Vis Rain Jacket - Type R Class 2



Specs

Product Code	<ul style="list-style-type: none">• R30RL05__ (Fluorescent Yellow)• R30RQ05__ (Fluorescent Orange)
Stock Sizes	SM-3X Other sizes available upon request
Stock Colors	
Made To Order Colors	
Fabric / Material	PU Coated FR Cotton

Compliance

Arc Rating 19 cal/cm² (Fluorescent Yellow) | 24 cal/cm² (Fluorescent Orange)

CAT Level CAT 2

ANSI Type / Class Type R Class 2

Standards

- NFPA 70E
- ANSI/ISEA 107 Type R Class 2
- ASTM F1891
- ASTM F2733
- CSA Z462
- OSHA 1910.269

Features

Features

- Waterproof welded seams with reinforced stress points to provide durability
- Batwing pattern creating freedom of movement
- Contoured collar with tuck away
- Covered zipper and snap closures
- FR hook and loop adjustable tab closures
- Back ventilation system with FR mesh for increased airflow
- Covered D-Ring opening access
- Two reinforced front pockets with FR hook and loop closure
- 2" silver reflective trim
- Adjustable cuffs
- Front storm flap with reflective trim
- FR polyurethane is durable and flexible that will not become brittle as it ages
- FR fabric will not melt, drip, or ignite
- Made in the USA

Product Care

Product Care

- READ THE GARMENT LABEL AND LAUNDER PER INSTRUCTIONS ON GARMENT LABEL.
- DO NOT Bleach.
- Wash/Laundering Instructions: Superficial dirt on the coating may be removed by wiping with a soft cloth moistened with warm, soapy water, then rinsed with plain water. More substantial dirt may need to be treated by wiping with alcohol, followed by warm water, then rinsed with plain water
- Drying: Air drying is preferred, but the product needs to be completely dried before storage to avoid possibly damaging the polyurethane coating.
- If contaminants cannot be removed after laundering, it is best to discontinue use of the garment.

Sizing Chart

Arc H20™ FR Rain Jacket (R30) / Trench Coat (R31) & FR Contractor Jacket (J30)			
Size	Chest	Sleeve Length*	Center Back Length
SM	34" - 37"	33.5"	R30 / J30 30.5" all sizes
MD	38" - 41"	34"	
LG	42" - 45"	34.5"	
XL	46" - 49"	35"	R31 48.5" all sizes
2X	50" - 53"	35.5"	
3X	54" - 57"	36"	



* Short: -3" off center back length & -1.5" off sleeve
 * Tall: +3" to center back length & +1.5" to sleeve



ATPV 19 & 24 CAL Arc H2O FR Hi-Vis Rain Bib Overall - Class E



Specs

Product Code	<ul style="list-style-type: none">• R40RL14__ (Fluorescent Yellow)• R40RQ14__ (Fluorescent Orange)
Stock Sizes	SM-3X Other sizes available upon request
Stock Colors	
Made To Order Colors	
Fabric / Material	PU Coated FR Cotton

Compliance

Arc Rating 19 cal/cm² (Fluorescent Yellow) | 24 cal/cm² (Fluorescent Orange)

CAT Level CAT 2

ANSI Type / Class Class E

Standards

- NFPA 70E
- ANSI/ISEA 107 Class E
- ASTM F1891
- ASTM F2733
- CSA Z462
- OSHA 1910.269

Features

Features

- Waterproof welded seams with reinforced stress points to provide durable construction
- FR fabric will not melt, drip or ignite
- FR polyurethane is durable and flexible that will not become brittle as it ages
- Convenient snap fly pant front
- Adjustable shoulder straps
- 2" silver reflective trim
- Adjustable elastic suspender system for fit and comfort
- Double storm flap that keeps weather out
- FR hook and loop tabs to adjust leg cuff
- Made in the USA

Product Care

Product Care

- READ THE GARMENT LABEL AND LAUNDRER PER INSTRUCTIONS ON GARMENT LABEL.
- DO NOT Bleach.
- Wash/Laundering Instructions: Superficial dirt on the coating may be removed by wiping with a soft cloth moistened with warm, soapy water, then rinsed with plain water. More substantial dirt may need to be treated by wiping with alcohol, followed by warm water, then rinsed with plain water.
- Drying: Air drying is preferred, but the product needs to be completely dried before storage to avoid possibly damaging the polyurethane coating.
- If contaminants cannot be removed after laundering, it is best to discontinue use of the garment.